



WASHER AND BRUSHER MACHINE FOR HAMS

TO WASH AND BRUSH HAMS AFTER SALT PROCESS



WASHER / BRUSHER OF HAMS LAVA-FAC-600

To brush and wash the hams is necessary in some steps of the ham cured process.

After salt process is necessary to take of the salt rests on the surface of ham.

After dry cured process, it's normal the mildews presences in the surface of the hams. Hams has not good aspect for the commercial chaine.

Machine with brushers, pressure water and moving sprayers, give us a final product without salt rests, without mildews and good aspect.

WASHER AND BRUSHER MACHINE FOR HAMS

TO WASH AND BRUSH HAMS AFTER SALT PROCESS

Once of ham is placed on the conveyor belt, it comes into the washing chamber where a system of sprinklers adapts to the surface of the ham and inject water at high pressure , at the same time brushers help us in this procees.

Salt is collected in tank placed underneath, and water is reused for the next ham.

Hams are washed by both sides and comes out of the machine ready to be hang.

- Closet washing circuit.
- Pump with draught filter.
- Independent hanging sprinklers.
- Water level control washing water in the tank.
- Rising with water direct from the mains.
- Stainless steel conveyor AISI 304.

Types	LAVAFAC-600
Length :	2. 020mm.
Width:	1.140 mm.
High:	1.530 mm.
Weight:	790 kg.
Power:	8 C.V.
Electrical consumption:	5,92 kW.
Conveyor motor power:	0,4 kW.
Washer pum power:	4 KW.
Washing pressure :	3 kg/cm ²
Water consumption :	1000 lts/h.
Ø water inlet :	1"
Production:	600 pieces/h.

